



FLIR GF300/GF320

Infrared Camera for Methane and VOC Detection

The FLIR GF300/GF320 is a revolutionary infrared camera capable of detecting Methane and Volatile Organic Compound (VOC) fugitive emissions from the production, transportation, and use of oil and natural gas. This camera can scan large areas and visualize potential gas leaks in real-time, so you can check thousands of components over the course of one survey. Designed with the user in mind, the GF300/GF320 is lightweight, offers both a viewfinder and LCD monitor, and has direct access to controls. Embedded GPS data helps in identifying the precise location of faults and leaks, for faster repairs.

Visualize Gas Emissions in Real-time

The FLIR GF300/GF320 is unbeatable at detecting gas emissions, with a High Sensitivity Mode that lets you visualize even the smallest leaks in real-time. Use this visual verification to pinpoint the exact source of the emissions and begin repairs immediately. In addition, the GF320 is capable of measuring temperatures up to 350 °C with ± 1 °C accuracy, allowing you to note temperature differentials and improve gas plume detection.

Increase Worker Safety

Surveys performed with GF300/GF320 cameras are nine-times faster than those performed with gas sniffers. They're also safer: optical gas imaging does not require close contact with components in order to detect gas. This reduces the risk of exposure to invisible and potentially harmful chemicals. In addition, the camera can scan areas of interest that are difficult to reach using conventional methods. The ergonomic design, with a bright LCD and articulated viewfinder, takes the strain out of a full day of surveys.

Stop Leaks, Save Money, Help the Environment

By fixing gas leaks, you can save your company thousands in lost gas and lost profits, while at the same time improving regulatory compliance and protecting the environment. The FLIR GF300/GF320 complies with all current regulations for Optical Gas Imaging (OGI). See our website for a full listing.

The GF300/GF320 detects the following gases:

Methanol	Methane	Benzene	Ethane	Propylene
Ethanol	Pentane	1-Pentene	Isoprene	Butane
Ethylbenzene	MEK	Toluene	Propane	Octane
Heptane	MIBK	Xylene	Ethylene	Hexane



Specifications

Model		GF300 / GF320
Detector Type	FLIR Indium Antimonide (InSb)	
Spectral Range	3.2 – 3.4 μ m	
Resolution	320 x 240 pixels	
Detector Pitch	30 μ m	
NETD/Thermal Sensitivity	<15 mK @ +30°C (+86°F)	
Sensor Cooling	Stirling Microcooler (FLIR MC-3)	
Electronics / Imaging		
Image Modes	IR Image, visual image, high sensitivity mode (HSM)	
Frame Rate (Full Window)	60 Hz	
Dynamic Range	14-bit	
Video Recording / Streaming	Real-time non-radiometric recording: MPEG4/H.264 (up to 60 min./clip) to memory card Real-time non-radiometric streaming: RTP/MPEG4	
Visual Video	MPEG4 (25 min./clip) to memory card	
Visual Image	3.2 MP from integrated visible camera	
GPS	Location data stored with every image	
Camera Control	Remote camera control via USB	
Measurement		
Standard Temperature Range	–20°C to +350°C (–4°F to +662°F)	
Accuracy*	\pm 1°C (\pm 1.8°F) for temperature range (0°C, to +100°C, +32°F to +212°F) or \pm 2% of reading for temperature range (>+100°C, >+212°F)	
Optics		
Camera f/number	f/1.5	
Available Fixed Lenses	14.5° (38 mm), 24° (23 mm)	
Focus	Automatic (one touch) or manual (electric or on the lens)	
Image Presentation		
On-Camera Display	Built-in widescreen, 4.3 in. LCD, 800 x 480 pixels	
Automatic Gain Control	Continuous/manual, linear, histogram	
Image Analysis*	10 spotmeters, 5 boxes with max./min./average, profile, delta temperatures, emissivity & measurement corrections	
Color palettes	Iron, Gray, Rainbow, Arctic, Lava, Rainbow HC	
Zoom	1-8x continuous, digital zoom	
General		
Operating Temperature Range	–20°C to +50°C (–4°F to +122°F)	
Storage Temperature Range	–30°C to +60°C (–22°F to +140°F)	
Encapsulation	IP 54 (IEC 60529)	
Bump / Vibration	25 g (IEC 60068-2-27) / 2 g (IEC 60068-2-6)	
Power	AC adapter 90-260 VAC, 50/60 Hz or 12 V from a vehicle	
Battery System	Rechargeable Li-ion battery	
Weight w/ Battery & Lens	1.94 kg (4.27 lbs)	
Size (L x W x H) w/ Lens	305 x 169 x 161 mm	
Mounting	Standard, 1/4"-20	

* GF320 model only



FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

PORTLAND
Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

EUROPE
FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

www.flir.com/ogi
NASDAQ: FLIR

CANADA
FLIR Systems, Ltd.
920 Sheldon Court
Burlington, ON L7L 5L6
Canada
PH: +1 800.613.0507

CHINA
FLIR Systems Co., Ltd
Rm 1613-16, Tower II
Grand Central Plaza
138 Shatin Rural
Committee Road Shatin
New Territories
Hong Kong
PH: +852 2792 8955

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18052-852
Brasil
PH: +55 15 3238 7080

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2015 FLIR Systems, Inc. All rights reserved. (Updated 11/03/15)