

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications
 Small form factor, rack mounted system
 Class A/AB Linear design
 High Power Advanced technology devices
 Instantaneous ultra-wide bandwidth
 Built-in protection circuits, with extensive monitoring
 Local LCD & remote flexible interfaces
 High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

| Parameter | Specification | Notes |
|------------------------------|--------------------------|------------------------------|
| Operating Frequency Range | 10 KHz - 250 MHz | |
| Power Output @ Psat | 300 Watt Min | CW |
| Power Output @ P1dB | 140 Watt Typ | |
| Power Gain | 55 dB Min | 0dBm or less for rated power |
| Power Gain Flatness | 4.0 dB p-p Max | Constant input power |
| Gain Adjustment Range | >25 dB Typ | Local or remote capable |
| Input Return Loss | -10 dB Max | |
| 2-Tone Intermodulation (IMD) | <-30 dBc Typ | 45dBm/Tone, Δ = 1MHz |
| Harmonics | <-20 dBc Typ | At rated output |
| Spurious | -60 dBc Max | Non-harmonic |
| Operating Voltage | 100 - 240 VAC | 47 - 63 Hz |
| Power Consumption | 1800 Watt Max | At rated output |
| Input Power Protection | +10 dBm Max ¹ | |
| Load VSWR Protection | 4 : 1: Max ² | Foldback @ preset limit |
| Sample Port (optional) | -50 dB | N-Female |

1 Units with optional digital monitor and control, for basic units <10 Sec without damage

2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

| Parameter | Specification | Notes |
|-------------------------------|-------------------------------|----------------|
| Operating Ambient Temperature | 0 to +50 °C | |
| Storage Temperature | -40 to +85 °C | |
| Relative Humidity | up to 95 % | Non-condensing |
| Altitude | 3000 meters | |
| Shock & Vibration | Normal transport ³ | |

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

| Parameter | Specification | Notes |
|--|--|-------------------------------------|
| Dimensions W x H x D | 483 x 178 x 600 mm | 4U, excluding handles |
| Weight | 28 kg Max | |
| RF Conn. In / Out / Sample | N-Female | Front or rear panel |
| Interface Connector | 9-Pin D-Sub | Rear panel |
| AC Power | IEC 60320-C14 | Or equivalent |
| Cooling | Built in Fan Cooling | Variable speed |
| OPTIONAL: Digital Monitor & Control (DMC) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT) | Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON | IEEE rear panel BNC-F rear panel |



AA-10K250M-300 SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

| Parameter | Specification | Notes |
|--|--|---------------------------------|
| Option FRS: Forward RF Sample | -50dB, Type N-Female | Front or rear panel |
| Option RRS: Reflected RF Sample | -40dB, Type N-Female | Front or rear panel |
| Option GPIB: GPIB remote control | GPIB IEEE-488 Remote capability | |
| Included CPM: Calibrated Power Monitoring | Offset correction entry for +/- 0.2dB accuracy | 11-points standard ⁴ |

⁴ Consult with factory if additional points would be required.