

ESD 30N

ELECTROSTATIC DISCHARGE SIMULATOR UP TO 30KV



FOR TESTS ACCORDING TO ...

- > Renault 36.00.808/--K
- > SAE J1113-13
- > SAE J1455
- > Smart DE1005B
- > VW TL 824 66









ESD 30N - GENERATES ESD PULSES ABOVE EN/IEC 61000-4-2 TEST LEVELS

Electrostatic discharges either from a human body to any other part or between two different objects can cause persistent disturbances or even destruction to sensitive electronics or controls. ESD 30N is an ESD tester to simulate ESD pulses at higher voltages up to 30kV in both air and contact discharge mode. It therefore satisfies requirements exceeding the EN/IEC 61000-4-2 test levels and complies to automotive test applications.

HIGHLIGHTS

- > Test voltage up to 30kV for air and contact discharge
- > Discharges up to 20Hz
- > Easy-to-change R/C-networks and tips
- > Bleed-Off function
- > Measurement of temperature and humidity
- > AC mains supply and DC supply
- > Battery operated
- > External trigger function

APPLICATION AREAS

- | | |
|---|--|
|  AUTOMOTIVE |  COMPONENTS |
|  INDUSTRY |  TELECOM |
|  MEDICAL |  RENEWABLE ENERGY |
|  BROADCAST |  MILITARY |
|  RESIDENTIAL |  AVIONICS |

TECHNICAL DETAILS

TEST LEVEL

Test voltage	200V - 30,000V \pm 5% for contact discharge
	200V - 30,000V \pm 5% for air discharge
Resolution	100V steps
Holding time (AD)	More than 5s

MAINFRAME ESD 30N

HV power supply	Up to 30kV DC
Power supply	88V - 250V AC 12V - 18V DC
Battery	Approx. 1 hour operation; Buffer battery is automatically recharged when connected to AC mains supply
Interface	USB to control the ESD generator and to download pre-programmed test routines from esd.control

DISCHARGE UNIT P 30N

	Hand held discharge unit
Controls	2 function keys and one control wheel
Display	Graphic LCD display
Test level	200V to 30,000V
Polarity	Positive, negative; selectable
Discharge mode	Air or Contact discharge, selectable
Discharge tip	Point and ball type
Indicators	Integrated sensor to measure temperature and rel. humidity

TRIGGER

Single pulse	Release of a single pulse
Multiple pulses	Continuous discharge up to 20Hz
Counter	0 - 9,999 for discharge pre-selection

OUTPUT

Contact Discharge Pulse	As per EN/IEC 61000-4-2; 150pF/330ohm
Rise time	As per EN/IEC 61000-4-2 Ed.2 0.8ns +/- 25%
First peak current value	As per EN/IEC 61000-4-2 Ed.2 7.5A \pm 15% @2kV 15A \pm 15% @4kV 22.5A \pm 15% @6kV 30A \pm 15% @8kV
Current value at 30ns	As per EN/IEC 61000-4-2 Ed.2 4.0A \pm 30% @2kV 8.0A \pm 30% @4kV 12.0A \pm 30% @6kV 16.0A \pm 30% @8kV
Current value at 60ns	As per EN/IEC 61000-4-2 Ed.2 2.0A \pm 30% @2kV 4.0A \pm 30% @4kV 6.0A \pm 30% @6kV 8.0A \pm 30% @8kV

GENERAL

Weight	Approx. 5.1kg (ESD 30N control unit)
Weight	Approx. 1,250g (P 30N discharge gun)
Supply voltage	AC: 88V - 264V, 50/60Hz DC: 11V - 16VDC
Fuses	2x 0.5A T

ACCESSORIES (INCLUDED)

	Discharge tips for AD and CD
	Grounding lead 2m
	Test certificate and instruction manual

TECHNICAL DETAILS

OPTIONS (NOT INCLUDED)	
RCN 1	150pF/330 Ohm discharge network
RCN 2	150pF/2000 Ohm discharge network
RCN 3	330pF/2000 Ohm discharge network
RCN 4	100pF/1500 Ohm discharge network
RCN 5	330pF/330 Ohm discharge network
RCN x	Customer specific discharge network
P 30N-30	30mm discharge electrode
VCP	Vertical coupling plane
EAS30	Grounding resistors 2 x 470kOhm
esd.control	Remote control and documentation software for ESD testing. Supports the creation of test plans and download of related test sequences into the ESD generator
OptoLink	Fiber optic link between dito and PC (USB port) fitted with USB A connector, length 3m or 6m, max. baud rate of 19,200.

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST (Switzerland) GmbH > Sternhofstraße 15 > 4153 Reinach > Switzerland
 Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199
 Internet: www.emtest.ch > E-mail: sales@emtest.ch

Germany

EM TEST GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland
 Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050
 Internet: www.emtest.com > E-mail: info@emtest.de

France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France
 Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55
 Internet: www.emtest.fr > E-mail: info@emtest.fr

Poland

EM TEST Polska > ul. Ogrodowa 31/35, 00-893 Warszawa > Polska
 Phone +48 (0)518 64 35 12
 Internet: www.emtest.com/pl > E-mail: info.polska@emtest.de

USA / Canada

EM TEST USA Inc. > 9250 Brown Deer Road > San Diego > CA 92121
 Phone +1 (858) 699 1685 > Fax +1 (858) 458 0267
 Internet: www.emtest.com > E-mail: tom.revesz@ametek.com

P.R. China

EM TEST Representative Office Beijing > Rm 913, Leftbank > No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China
 Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38
 Internet: www.emtest.com > E-mail: emtestbj@public.bta.net.cn

Malaysia

EM TEST (M) SDN BHD > Unit B2-6, Jalan Dataran SD2 > Dataran SD2, PJU9 > Bandar Sri Damansara > 52200 Kuala Lumpur > Malaysia
 Phone +60 (03)62 73 22 01 > Fax +60 (03)62 74 22 01
 Internet: www.emtest.com > E-mail: sales@emtest.com.my

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Technical data subject to change without further notice.