

Advanced Test Equipment Rentals www.atecorp.com 800-404-ATEC (2832)



Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com www.AHSystems.com

SAS-517 Log Periodic Antenna 80 MHz – 4 GHz

This directional Log Periodic Antenna is an ideal solution for radiated emissions and normalized site attenuation.





Frequency Range: 80 MHz - 4000 MHz

Maximum Continuous Power: 1000 Watts

Impedance: 50 Ω Max Radiated Field: 200 V/m

Connector: N-Type, female

Mounting Base: 1/4 - 20 Thread, female

Features

- Frequency Range of 80 MHz to 4000 MHz
- Receive and Transmit
- Individually Calibrated (1, 3 and 10 Meter calibration included, horizontal polarization)
- Rugged Construction, supplied with LPM-510 mounting adapter
- Three Year Warranty

The A.H. Systems' SAS-517 Log Periodic Antenna is lightweight, compact and has been manufactured to ensure maximum gain and low VSWR. This directional antenna has a broad range of application, from compliance testing to surveillance. Whether testing inside a shielded enclosure or outdoors, this antenna will display efficient performance characteristics through the frequency range of 80 MHz to 4000 MHz.


Recommended Accessories


- ATU-510 (Antenna Tripod, Wooden)
- AEH-510 (Azimuth and Elevation Head)
- PAM-0204 (25 dB Preamplifier)



Tel: (818) 998-0223 Fax: (818) 998-6892


sales@AHSystems.com www.AHSystems.com





Tel: (818) 998-0223 Fax: (818) 998-6892 sales@AHSystems.com

www.AHSystems.com



Physical Dimensions:

Length: 56.6 in. (143.8 cm)
Width: 72.3 in. (183.6 cm)
Weight: 4.6 lb.'s (2.09 kg)