



Measuring electric fields from 600 MHz to 6 GHz

using instruments in the NBM-500 family

- ▲ **Field exposure from mobile radio and wireless LAN signals**
- ▲ **Suppression of broadcast signals below 600 MHz**
- ▲ **Isotropic (non-directional) measurement**
- ▲ **70 dB dynamic without changing range**
- ▲ **High sensitivity starting at 0.2 V/m**

The probe contains three orthogonally arranged dipoles with detector diodes. The three voltages, corresponding to the spatial components, are available individually at the probe output. The NBM basic unit calculates the resulting isotropic field strength.

APPLICATIONS

The probe detects electric fields from 600 MHz to 6 GHz and is thus particularly suitable for measuring the field strength generated by mobile radio base stations and wireless LAN systems. Due to its high dynamics and sensitivity of 0.2 V/m, the probe can detect even low field strengths accurately. The probe exceeds the requirements of the basic standards EN 50492, IEC 62232 and HJ 972-2018 (China), but uses a band limitation that suppresses electromagnetic fields below 600 MHz.

PROPERTIES

The probe is designed with mechanical and electrical properties ideal for field use. The probe head is made of foam material to provide effective protection for the sensors, while having excellent RF characteristics.

CALIBRATION

The probe is calibrated at several frequencies. The correction values are stored in an EPROM in the probe and are automatically taken into account by the NBM instrument. Calibrated accuracy is thus obtained regardless of the combination of probe and instrument.



SPECIFICATIONS ^a




Probe EF0692		Electric (E-)Field	
Frequency range ^(b)	600 MHz to 6 GHz		
Type of frequency response	Flat		
Measurement range	0.2 to 650 V/m (CW) 0.2 to 22 V/m (True RMS)	10 nW/cm ² to 112 mW/cm ² (CW) 10 nW/cm ² to 0.13 mW/cm ² (True RMS)	
Dynamic range	70 dB		
CW damage level	1000 V/m	265 mW/cm ²	
Peak damage level, typical ^(c)	10 kV/m	26 W/cm ²	
Sensor type	Diode based system		
Directivity	Isotropic (Tri-axial)		
Readout mode / spatial assessment	3 separate axes		
UNCERTAINTY			
Flatness of frequency response ^(d) Calibration uncertainty not included	±1.5 dB (700 MHz to 3 GHz) +2.5/ -1.5 dB (> 3 GHz to 5 GHz)		
Linearity Referred to 0.2 mW/cm ² (27.5 V/m)	±0.5 dB (2.2 to 316 V/m)	±0.5 dB (0.0013 to 26.5 mW/cm ²)	
Isotropic response ^(e)	±1 dB (600 MHz to 4 GHz) ±1.5 dB (> 4 GHz to 6 GHz)		
Temperature response	+0.2/ -1 dB (0 °C to 50 °C, related to 23 °C)		
GENERAL SPECIFICATIONS			
Factory calibration frequencies	0.25/ 0.4/ 0.6/ 0.65/ 0.7/ 0.8/ 0.9/ 1/ 1.4/ 1.8/ 2.1/ 2.45/ 2.7/ 3/ 3.5/ 4/ 5/ 6 GHz		
Recommended calibration interval	24 months		
Temperature range			
Operating	0 °C to +50 °C		
Non-operating (transport)	-40 °C to +70 °C		
Humidity	5 to 95 % RH @ ≤25 °C	≤23 g/m ³ absolute humidity	
Size	318 mm x 66 mm Ø		
Weight	90 g		
Compatibility	NBM-500 series meters		
Country of origin	Germany		

- (a) Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23±3 °C, relative air humidity 25% to 75%, sinusoidal signal
 (b) Cutoff frequency at approx. -3 dB
 (c) Pulse length 1µsec, duty cycle 1:100
 (d) Frequency response can be compensated for by the use of correction factors stored in the probe memory
 (e) Results are calculated from the maximum and minimum response obtained during the full revolution about the stem of the probe, oriented 54.7° to the electric field vector.

ORDERING INFORMATION

	Part number
Probe EF0692, E-Field, for NBM, 600MHz-6GHz, Isotropic	2402/20B
Probe EF0692, E-Field, ACC - with accredited (DAkkS) calibration, basic unit required	2402/20B/ACC

CHARACTERISTICS



Narda Safety Test Solutions GmbH
Sandwiesenstrasse 7
72793 Pfullingen, Germany
Phone +49 7121 97 32 0
info@narda-sts.com

Narda Safety Test Solutions
North America Representative Office
435 Moreland Road
Hauppauge, NY11788, USA
Phone +1 631 231 1700
info@narda-sts.com

Narda Safety Test Solutions S.r.l.
Via Rimini, 22
20142 Milano, Italy
Phone +39 0258188 1
nardait.support@narda-sts.it

Narda Safety Test Solutions GmbH
Beijing Representative Office
Xiyuan Hotel, No. 1 Sanlihe Road, Haidian
100044 Beijing, China
Phone +86 10 6830 5870
support@narda-sts.cn

www.narda-sts.com

© Names and Logo are registered trademarks of Narda Safety Test Solutions GmbH - Trade names are trademarks of the owners.