



25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA



TECHNICAL DATA SHEET

PE15A3008

PE15A3008 is a broadband GaAs PHEMT MMIC-based coaxial power amplifier, operating in the 0.5 to 18 GHz frequency range. The amplifier offers 25 dBm of P1dB and 27 dB small signal gain, with gain flatness of ± 2.5 dB along with an outstanding 35 dBm of IP3 performance. This power amplifier requires only a single positive DC supply, is unconditionally stable, operates over the temperature range of -40°C to 75°C , and characterized by a light weight (28 g) and small size (1.5"x1.0"x0.4").

Features

- 0.5 to 18 GHz Frequency Range
- P1dB: 25 dBm
- Small Signal Gain: 27 dB
- Gain Flatness: ± 2.5 dB
- Gain Variation Over the Temperature Range: ± 2 dB
- Output IP3: 35 dBm
- Noise Figure Range: 2.5-4 dB
- 50 Ohm Input and Output Matched
- -40 to $+75^{\circ}\text{C}$ Operating Temperature
- Unconditionally Stable
- Single DC Positive Supply
- Built-in DC Voltage Regulator
- Small Size & Light Weight

Applications

- Laboratory Applications
- R&D Labs
- Radar Systems
- Electronic Warfare
- Telecom Infrastructure
- Test Instrumentation
- Military & Space
- Communication Systems
- Satellite Communications
- Wireless Communications
- Unmanned Systems
- Microwave Radio Systems
- Power Amplifier
- Low Noise Amplifier
- General Purpose Amplification
- RF Front Ends

Electrical Specifications (TA= 25°C, VDC1 = 12 Vdc)

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.5		18	GHz
Gain	23	27	30.5	dB
Gain Flatness		± 2.5	± 2.75	dB
Gain Variation over OTR*		± 2	± 2.5	dB
Output at 1 dB Compression Point	+23	+25		dBm
Output 3 rd Intercept Point	+30	+35		dBm
Spurious			-60	dBc
Noise Figure		3		dB
Noise Figure at 500 to 700 MHz		4	4.5	dB
Noise Figure at 0.7 to 18 GHz		2.5	3.5	dB
Input VSWR		1.8:1	2.5:1	
Output VSWR		1.5:1	2:1	
Operating DC Voltage 1		12		Volts
Operating DC Current	300	330	500	mA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA PE15A3008](#)



25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA

TECHNICAL DATA SHEET

PE15A3008

Operating Temperature Range (OTR) -40 +75 °C

*OTR= Base Plate Operating Temperature Range

Absolute Maximum Rating

Parameter	Rating	Units
Source Voltage	+13	Volts
RF input Power	+15	dBm
Operating Temperature	-40 to +75	°C
Storage Temperature	-55 to +125	°C



ESD Sensitive Material,
Transport material in
Approved ESD bags.
Handle only in approved
ESD Workstation.

Mechanical Specifications

Size

Length	1.5 in [38.1 mm]
Width	1 in [25.4 mm]
Height	0.4 in [10.16 mm]
Weight	0.065 lbs [29.48 g]
Input Connector	SMA Female
Output Connector	SMA Female

Environmental Specifications

Temperature

Operating Range	-40 to +75 deg C
Storage Range	-45 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA PE15A3008](#)



25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA

TECHNICAL DATA SHEET PE15A3008

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA PE15A3008](#)



25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA

TECHNICAL DATA SHEET

PE15A3008

25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA PE15A3008](https://www.pasternack.com/18-ghz-medium-power-broadband-amplifier-27-db-gain-35-dbm-ip3-3-db-nf-sma-pe15a3008)

URL: <https://www.pasternack.com/18-ghz-medium-power-broadband-amplifier-27-db-gain-35-dbm-ip3-3-db-nf-sma-pe15a3008-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE15A3008 CAD Drawing

25 dBm P1dB, 500 MHz to 18 GHz, Medium Power Broadband Amplifier, 27 dB Gain, 35 dBm IP3, 3 dB NF, SMA



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.01
.XXX	±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE15A3008

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAGE CODE 53919

CAD FILE 11/19/18

SCALE N/A

SIZE A

7361