

EFT 500N8

ELECTRICAL FAST TRANSIENT GENERATOR



FOR TESTS ACCORDING TO ...

- > EN 61000-4-4
- > EN 61000-6-1
- > EN 61000-6-2
- > IEC 61000-4-4
- > IEC 61326
- > IEC 61850-3

EFT 500N8 - EFT/BURST TESTER

The EFT 500N8 is the state-of-the-art EFT/Burst tester with a built-in coupling/decoupling network for single phase or three-phase mains supply lines and a HV terminal to connect a capacitive coupling clamp.







The spike frequency can be varied from as low as 100Hz to 1,000kHz. The EFT 500N8 is capable to generate 1,000 spikes per second or up to 150 spikes per burst.

Its performance fully complies with IEC 61000-4-4:2004, IEC 61000-4-4 Amd.1 Ed.2:01/2010 and IEC 61000-4-4 Ed.3: 03/2012. Pre-programmed Standard Test routines and a number of selected User Test routines make the EFT 500N8 an optimum standalone solution for both testing during development and final testing of products and sub-assemblies.

HIGHLIGHTS

- > **Standalone Tester**
- > **7,000V Burst voltage**
- > **Spike frequency 1MHz**
- > **Built-in 1ph or 3ph coupler**
- > **USB (optical link) and GPIB interface**
- > **Standard Test routines**

APPLICATION AREAS

- | | |
|---|--|
|  INDUSTRY |  TELECOM |
|  MEDICAL |  COMPONENTS |
|  BROADCAST | |
|  RESIDENTIAL | |

TECHNICAL DETAILS

EFT 500N8 MODELS

EFT 500N8	With 1-phase coupler; 250V/16A
EFT 500N8.1	With 3-phase coupler; 3 x 440V/32A
	Other couplers on special request

TEST LEVEL

Voltage range	1,000V - 7,000V
Into 50ohm	500V - 3,500V
Pulse shape	5/50ns into 50ohm load
Rise time tr	5ns ± 30%
Pulse width td	50ns ± 30%
Pulse shape	5/50ns into 1,000ohm load
Rise time tr	5ns ± 30%
Pulse width td	35ns to 150ns
Source impedance	50ohm ± 20%
Polarity	Positive/negative

TRIGGER

Automatic	Automatic release of the bursts
Manual	Manual release of a single pulse
External	External release of a single pulse
Burst duration	Td = 0.1ms - 999.9ms
Burst repetition rate	Tr = 10ms - 9,999ms/man Tr ≤ 9,999ms ⇒ Auto Trigger Tr > 9,999ms ⇒ Man Trigger
Spike frequency	f = 0.1kHz - 1,000kHz
Test duration	T = 0:01 min - 99:59 min T > 99:59 min - endless

OUTPUT

Direct	Via HV coax connector
Coupler	L, N and PE, all combinations
DUT supply AC	250V/16A, 50/60Hz
DUT supply DC	250V/10A
DUT supply	Other DUT supply voltages on request
CRO Trigger	15V trigger signal for oscilloscope; burst duration and pulse frequency can be checked

TEST ROUTINES

Quick Start	Immediate start; easy-to-use and fast
User Test routines	<ol style="list-style-type: none"> 1. Custom made test routines 2. Change voltage after T 3. Change frequency after T 4. Frequency sweep within a burst 5. Change burst duration after T 6. Randomly released bursts 7. Synchronous burst mode 8. Change polarity after T
Standard Test routines	<ol style="list-style-type: none"> 1. As per IEC 61000-4-4, Level 1-5 2. Automatic test Level X to level Y
Service	Service, set-up, self test

INTERFACES

Optical interface	Opto link, 3 m cable USB A connector
Parallel interface	IEEE 488, address 1 - 30
CN interface	To control external CNI 503

GENERAL DATA

Dimensions, weight	EFT 500N8: 19"/3HU, approx. 15kg EFT 500N8.1: 19"/6HU, approx. 19kg
Supply voltage	115/230V +10/-15%
Fuses	2x T 2AT (230V); 2x T 4AT (115V)

TECHNICAL DETAILS

OPTIONS	
HFK	Coupling clamp as per IEC 61000-4-4
ADA 800	SHV-Adapter for HFK connection
KW 50	50ohm matching resistor for verification
KW 1000	1,000ohm matching resistor for verification
6dB	6dB attenuator
CNI 503	Coupling/decoupling networks, 3x440V/32-63-100A
iec.control	Software to control the test, including standard library, test report facility and data conversion generator
CA EFT kit	Kit for burst pulse verification consisting of KW50, KW1000 and adapter for EUT port in a plastic case for storage

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST (Switzerland) GmbH > Sternenhofstraße 15 > 4153 Reinach > Switzerland
Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199
Internet: www.emtest.ch > E-mail: sales.emtest@ametek.com

Germany

EM TEST GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland
Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050
Internet: www.emtest.com > E-mail: info.emtest@ametek.de

France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France
Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55
Internet: www.emtest.fr > E-mail: info@emtest.fr

Poland

EM TEST Polska > ul. Ogrodowa 31/35, 00-893 Warszawa > Polska
Phone +48 (0)518 64 35 12
Internet: www.emtest.com/pl > E-mail: info_polska.emtest@ametek.de

USA / Canada

EM TEST USA > 9250 Brown Deer Road > San Diego > CA 92121
Phone +1 (858) 699 1685 > Fax +1 (858) 458 0267
Internet: www.emtest.com > E-mail: sales.emtest@ametek.com

P.R. China

E & S Test Technology Limited > Rm 913, Leftbank > No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China
Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38
Internet: www.emtest.com > E-mail: info@emtest.com.cn

Republic of Korea

EM TEST Korea Limited > #405 > WooYeon Plaza > #986-8 > YoungDeok-dong > Giheung-gu > Yongin-si > Gyeonggi-do > Korea
Phone +82 (31) 216 8616 > Fax +82 (31) 216 8616
Internet: www.emtest.co.kr > E-mail: sales@emtest.co.kr

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Technical data subject to change without further notice.