

Technical data

Provided by:



www.atecorp.com
(800) 404-ATEC

MPD 800 system

Rentals • Sales • Calibration • Service

MPD 800

Input

Voltage	PD input: 80 V _{peak}
Current	PD input (max. RMS continuous) ¹ : 250 mA AC input (max. RMS continuous): 150 mA AC input (min. RMS): 20 nA
Impedance	PD input: 50 Ω ± 20 % AC input (f < 4 kHz): 5 Ω ± 20 %
Ports	PD input: 2 × BNC AC input: 2 × BNC
Dynamic range	PD input: 140 dB (overall), 70 dB (per range) AC input: 170 dB (overall), 107 dB (per range)
Levels	PD input: 14 AC input: 5

Frequency range

PD input internal quadripole	Enabled: 6 kHz ... 35 MHz Disabled: 0 Hz ... 35 MHz
AC input	DC, 0.1 Hz ... 10 kHz

Accuracy

PD input	± 2 %
AC input	0.02 %
Frequency	± 1 ppm

PC requirements

Interface	USB 3.0
Hardware	Minimum ² : Quad-Core 64-bit Intel or AMD CPU with at least 1.6 GHz, 4 GB RAM (e.g. Intel i5, AMD Ryzen 3) Recommended ³ : Quad-Core 64-bit Intel or AMD CPU with at least 2.5 GHz, 8 ... 16 GB RAM, dedicated GPU (e.g. Intel i7, AMD Ryzen 5) High-End ⁴ : Octa-Core 64-bit Intel or AMD CPU with at least 3.2 GHz, 32 GB RAM, dedicated GPU (e.g. Intel i7/i9, AMD Ryzen 7)
Software	Windows 8™, Windows 8.1™, Windows 10™ (all 64-bit)

¹ Internal CPL

² For example, for 1 × MPD 800 for "pass/fail" testing

³ For example, for 1 to 4 × MPD 800 including 3PAR, PD fault localization and channel gating

⁴ For example, for multi-units up to 20 measurement channels

⁵ Fixed filter (100 kHz-1 MHz)

⁶ Time domain integration

Output

Optical trigger port	1 × ST (820 nm), OM2, FO cable length ≤ 50 m
OUT port	1 × BNC, 50 Ω ± 10 %, 5 V ± 0.5 %
AUX port	For MBB1 support

Fiber-optic ports

Wavelength	1308 nm
Connector type (FO1, FO2)	2 × LC (interchangeable)

PD data processing

Time domain	56 ns ... 8 μs
PD sampling rate	125 MS/s
Resolution	PD: 14 bits AC: 24 bits
PD pulse rate	Max.: 2 Mio./s
PD filters/bandwidths	RIV: 4.5 kHz and 9 kHz Charge: 30 kHz, 100 kHz, 200 kHz, 300 kHz, 400 kHz, 600 kHz, 900 kHz ⁵ , 1 MHz, 2 MHz, 5 MHz, 10 MHz, 20 MHz
PD input low-pass filters	1.1 MHz, 2.3 MHz, 4.7 MHz
PRPD pre-recording time	0s ... 30 s
PD scope	Recording depth: 131 μs Refresh rate: 41 ms
PD event time resolution	< 2 ns
System noise	Typical ⁶ : < 0.010 pC
Spectrum analyzer noise (100 kHz ... 5 MHz)	< 140 dBm
Max. double pulse resolution (BW = 20 MHz)	< 100 ns
Negativ superposition error	< 3 %

Mechanical data and ambient conditions

Humidity	5 % ... 95 %, non-condensing
Operation temperature	-20 °C ... 55 °C / -4 °F ... 89 °F
Dimensions (W × H × D)	119 × 190 × 55 mm / 4.7 × 7.5 × 2.2 in
Weight	870 g / 1.9 lbs

Protection specifications

Input surge current withstand capability PD input (8/20 μ s, 10 operation)	20 kA
Input surge current withstand capability PD input (1 s, 50 Hz, 10 operations)	20 A
Input surge current withstand capability AC input (100 s, 50 Hz, 1000 operations)	5 A

Equipment reliability

Shock	IEC/EN 60068-2-27
Vibration	IEC/EN 60068-2-6
Damp heat	IEC/EN 60068-2-78
Ingress protection (IEC/EN 60529)	IP4x
Temperature changes	IEC/EN 60068-2-14
Dry heat	IEC/EN 60068-2-2
Cold	IEC/EN 60068-2-1
EMV	IEC/EN 61326-1 (industrial electromagnetic environment) FCC subpart B of part 15, class A
Safety	IEC/EN/UL 61010-1 IEC/EN/UL 61010-2-030
Laser class	EN 60825-1:2007 EN 60825-2:2007

Certificates

IEC 60270 type test

MCU2 – Multi-device control unit

The controller MCU2 converts optical signals transmitted by a fiber-optic cable to standard electrical communication signals.

Interface	USB 3.0
Fiber-optic (FO) network	For MPD 800: LC For MPD 600: ST
Connector type	2 \times LC (FO1, FO2) 1 \times ST pair (FO3)
Max. FO cable length	2.5 km / 15.5 mi

Mechanical data

Dimensions (W \times H \times D)	119 \times 175 \times 55 mm / 4.7 \times 6.9 \times 2.2 in
Weight	750 g / 1.7 lbs

RBP1 – Lithium-ion battery pack

The RBP1 is a rechargeable battery pack for operating the MPD 800, including a battery status display. Up to five RBP1 can be connected to power long-time PD measurement setups.

Operating time for MPD 800 with RBP1	At -20 $^{\circ}$ C / -4 $^{\circ}$ F:	13 hours
	At 23 $^{\circ}$ C / 73 $^{\circ}$ F:	16 hours
	At 55 $^{\circ}$ C / 131 $^{\circ}$ F:	16 hours
Typical charging duration	< 4 hours	
Battery lifecycle	1 000 cycles or 5 years ⁵	
Nominal voltage	11.1 V	
Nominal energy	96.6 Wh	

Power supply

Battery charge voltage	8 V DC ... 12.4 V DC
Power supply voltage	100 V ... 240 V (50 Hz ... 60 Hz)

Mechanical data

Dimensions (W \times H \times D)	115 \times 38 \times 175 mm / 4.5 \times 1.5 \times 6.9 in
Weight	910 g / 2 lbs

⁵ Whichever occurs first, remaining 50 % state of health (SoH) equals 40 Wh remaining energy.

Technical data

MPD 800 accessories

CAL 542 – Charge calibrator/injector

The CAL 542 charge calibrator is used to inject a defined charge into and verify the measurement circuit.

Technical data

Pulse repetition frequency	300 Hz
Pulse rise time	< 4 ns ¹
Dimensions (W x H x D)	110 x 30 x 185 mm / 4.3 x 1.2 x 7.3 in
Weight	520 g / 1.2 lbs (incl. battery)
Output connector	1 x BNC (with BNC adapter, cables and connection clamps)
Power supply	Lithium Battery 9 V, Lifetime > 10 years

¹ Typical value for type A and B

RIV1 – RIV Test calibrator

The RIV1 calibrator enables the reliable calibration of the MPD system for PD measurement based on Radio Influence Voltage (RIV) according to NEMA and CISPR standards.

Technical data	RIV1-NEMA	RIV1-CISPR
Frequency range	100 kHz ... 2 MHz (50 kHz steps)	100 kHz ... 2 MHz (50 kHz steps)
Magnitude	10 μV ... 10 mV	10 μV ... 10 mV @ 300 Ω
Magnitude accuracy	< 2 %	< 2 %
Output impedance	< 2 Ω	20 kΩ
Standards met	NEMA 107 - 1987, IEEE C57.12.90-2008	IEC 60437, CISPR 18-2 (2)
Accessory	CPL 542 NEMA 0.5 A, CPL 542 NEMA 1.2 A	CPL 542 CISPR 0.5 A, CPL 542 CISPR 1.2 A
Connectors	1 x BNC	
Dimensions (W x H x D)	120 x 40 x 183 mm / 4.7 x 1.6 x 7.2 in	
Weight	680 g / 1.5 lbs	
Temperature	Operating: 0 °C ... 50 °C / -4 °F ... 122 °F Storage: -20 °C ... 70 °C / 14 °F ... 158 °F	
Humidity	10 % ... 95 %, non-condensing	

CPL1/CPL2 – Measuring impedance

The CPL1/2 quadripoles are external measuring impedances (coupling device) for PD measurements. All CPL1/2 versions include surge current withstand capability of up to 8 kA.

Technical data	IEC	NEMA/IEC/CISPR	CISPR/IEC
Max. input current	7 A	7 A	7 A
Min. input current	5 μA	5 μA	5 μA
Input impedance	50 Ω ± 20 %	150 Ω ± 20 %	300 Ω ± 13 %
PD frequency range (-6 dB resp. 1 MHz)	5 kHz ... 35 MHz	20 kHz ... 40 MHz	35 kHz ... 2 MHz
Dimensions (W x H x D)	119 x 175 x 55 mm / 4.7 x 6.9 x 2.2 in		
Weight	1.3 kg / 2.8 lbs		

MBB1 – Measurement balanced bridge

The MBB1 is used to obtain reliable PD measurements in test environments with heavy interference. It enables you to perform differential PD measurements as recommended by IEC 60270.

Technical data	
Frequency range	100 kHz ... 1 MHz
Maximum voltage input	60 V _{rms}
Maximum PD voltage inputs	10 V _{rms}
Input connections	3 x BNC (PD-1, PD-2, V)
Output connections	2 x BNC (PD, V)
Control and power supply	via AUX-connection to MPD 600 or MPD 800
Dimensions (W x H x D)	110 x 190 x 44 mm / 4.3 x 7.5 x 1.7 in
Weight	650 g / 1.4 lbs

MCC – Coupling capacitor

The coupling capacitor connects the MPD system to the high-voltage test object. Different MCC coupling capacitors are available for various voltage levels.

Technical Data	MCC 112	MCC 117-C	MCC 124-C	MCC 210
$U_{\text{phase-to-ground (RMS)}}$	12 kV	17.5 kV	24 kV	100 kV
C_{nominal}	1.2 nF ($\pm 20\%$)	2 nF ($\pm 15\%$)	1.0 nF ($\pm 15\%$)	1.0 nF ($\pm 10\%$)
Withstand voltage (1 min)	28 kV	38 kV	50 kV	120 kV
Q_{PD}	< 2 pC @ 13.2 kV	< 2 pC @ 20.7 kV	< 2 pC @ 26.4 kV	< 1 pC @ 100 kV
Weight	4.5 kg / 9.9 lbs	2.3 kg / 5.1 lbs	3.2 kg / 7.1 lbs	10 kg / 22.1 lbs
Dimensions (W x H x D)	182 x 158 x 182 mm / 7.2 x 6.2 x 7.2 in	104 x 150 x 165 mm / 4.1 x 5.9 x 6.5 in	150 x 219 x 150 mm / 5.9 x 8.6 x 5.9 in	450 x 766 x 450 mm / 17.5 x 30.15 x 17.5 in
Scope of delivery	Adapter (TNC to BNC), BNC connection cable	Adapter (TNC to BNC), BNC connection cable	Adapter (TNC to BNC), BNC connection cable	BNC connection cable
Connection type	Directly connected to MPD 800	Directly connected to MPD 800	Directly connected to MPD 800	Directly connected to MPD 800

BTA kits – Bushing tap adapters

The following BTA kits consist of a BTA adapter that connects to the specific measurement tab and includes a gas discharge tube. The kits also include a BTA to BNC adapter and a coaxial cable that connects either via CPL or directly to the MPD system.

Technical Data

BTA3 kit	G 3/4" inside thread, 4 mm female connector (e.g. for ABB / Micafil standard, RTKF, RTKG)
BTA6 kit	2 1/4" – 12 UN outside thread, 8 mm female connector for IEEE standard (C57.19.01 - 2000 bushing measurement tab, e.g. HSP, ABB type O plus C)
BTA7 kit	M30 x 1.5 outside thread, 4 mm female connector (e.g. for HSP type SETF)
BTA9 kit	3/4" – 14 NPSM outside thread, spring contact interface (e.g. for ABB type T)
BTA14 kit	M24 inside thread, 4 mm male connector (e.g. for F&G or HSP type EKTF)

MCT 120 – High frequency CT

The MCT 120 is a high-frequency current transformer (HFCT), which picks up PD signals in moderate heights and at a safe distance from high-voltage.

Technical Data

Frequency range (-6 dB)	80 kHz ... 40 MHz (0 mm gap)
Inner hole dimensions	$\varnothing \sim 53.5$ mm / 2.1 in
Outer dimensions	114 x 154 x 62 mm / 4.5 x 6.1 x 2.5 in
Ferrite core	Split
Connector	BNC, 50 Ω , female
Weight	1.2 kg / 2.7 lbs
Operating temperature	-20 °C ... 55 °C / -4 °F ... 130 °F

Technical data

MPD 800 accessories

UHF 800 (Available 2021)

The UHF 800 is an ideal PD measurement solution for measuring power transformers and gas-insulated substations (GIS). It measures in the very high frequency (VHF) and ultra-high frequency (UHF) ranges. The UHF 800 is connected to the MCU2 or MPD 800 units and can be used together with UVS 610, UCS1 and UHT1 sensors, as well as most of the pre-installed UHF PD sensors for GIS.

Technical Data

UHF input range fc	100 MHz – 2 GHz
Measuring bandwidth Δf	Broadband and narrowband modes
Impedance UHF input	50 Ω (N-type input jack)
RF pre-amplifier	Switchable +20 dB and attenuator
Synchronization via UHF sensor	10 Hz ... 100 Hz

Mechanical Data

Connector type (FO1, FO2)	2 x LV (interchangeable)
Wavelength	1308 nm
Connectivity	FO series connection with MPD 800 units
Power supply	Powered by RBP1 battery
Dimension (W x H x D)	119 x 190 x 55 mm / 4.7 x 7.5 x 2.2 in
Ambient temperature	-20 °C ... 55 °C / -4 °F ... 89 °F
Relative humidity	5 % ... 95 %, non-condensing

UHT1 – Hatch-type UHF sensor

The UHT1 is a hatch-type sensor used for detecting PD inside power transformers in the ultra-high frequency (UHF) range. It is installed permanently on the surface of a tank of oil-paper-insulated power transformers, which do not have oil drain valves for a UVS 610.

Technical Data

Frequency range	200 MHz ... 1 GHz
Leakage tightness	For oil temperatures of -15 °C ... 120 °C / 5 °F ... 248 °F at 5 bar pressure
Operating temperature	-15 °C ... 120 °C / 5 °F ... 248 °F
Storage temperature	-15 °C ... 70 °C / 5 °F ... 158 °F
Humidity	5 % ... 95 % (non-condensing)
Dimensions (\varnothing x h)	150 x 109 mm / 5.9 x 4.3 in
Insertion depth	28 mm / 1.1 inch from flange to oil barrier
Weight	5 kg / 11 lbs
UHF (output)	Coaxial RF connector (TNC socket)
TEST (input)	Coaxial RF connector (type N socket)

UVS 610 – UHF valve sensor

The UHF valve sensor allows PD measurements in high-frequency ranges in power transformers with liquid insulation. It is inserted through the oil drain valve (DN 50 and DN 80).

Technical Data

Usable frequency range	150 MHz ... 1 GHz
Tightness	Up to 5 bar pressure -15 °C ... 120 °C / 5 °F ... 248 °F
Insertion depth	55 mm ... 450 mm / 2.2 in ... 17.7 in
Weight	3.1 kg / 6.8 lbs
Dimensions (\varnothing x H)	200 x 610 mm / 7.9 x 24 in

UPG 620 – Pulse generator

The UPG 620 generates very fast slope pulses and is mainly used to verify the measurement circuit in the UHF range.

Technical Data

Rise time	< 200 ps
Decay time	> 100 ns
Frequency repetition rate	100 Hz
Power supply	2 x 9 V lithium battery for > 120 h continuous operation
Weight	700 g / 1.5 lbs
Dimensions (W x H x D)	110 x 28 x 185 mm / 4.3 x 1.1 x 7.3 in
Operating temperature	0 °C ... 55 °C / 35 °F ... 130 °F

UCS1 – UHF cable sensor

This sensor performs PD measurements in UHF ranges in grounding systems of high-voltage cables and cable terminations.

Technical Data

Frequency range	100 MHz ... 1 000 MHz
Capacitance	2 nF
Insulation level	12 kV
AC withstand voltage	28 kV; 1 min.
Operating temperature	-20 °C ... 85 °C / -4 °F ... 185 °F
Dimensions (\varnothing x H)	105 x 107 mm / 4.1 x 4.2 in
Weight	1.2 kg / 2.6 lbs
Primary connections	Screw thread 2 x M8x14
Connector	TNC