

# SOLAR LINE IMPEDANCE STABILIZATION NETWORK


## SOLAR TYPE 9331-50-PJ-200-N SOLAR TYPE 9331-50-TS-200-N

**Specifications:**

Current rating: ..... 200 amperes  
 Inductance: ..... 50  $\mu$ H  
 Frequency range (recommended): ..... PJ 10 kHz – 30 MHz, TS 10 kHz – 50 MHz  
 Voltage (line to ground): ..... 800 VDC, 500 V 50-60 Hz, 240 V 400 Hz  
 Power connections: ..... PJ Supercon plug and jack, TS 3/8-16 threaded stud  
 RF connector: ..... Type N  
 Coupling capacitor: ..... 0.25  $\mu$ F  
 Circuit: ..... Single  
 Case size: ..... 10.29" x 9.25" x 13.00" (26.14 cm x 23.50 cm x 33.02 cm)  
     Overall length with base plate: 17.00" (43.18 cm). Equipped with 6.50" (16.51 cm)  
     50-60 Hz ventilating fan. Specify voltage: 110V/115 V or 220V/230V  
     Overall length with base plate and fan overhang: 21.50" (54.61 cm)

**Remarks:** Designed for MIL-STD-461D/E/F/G. Specifications subject to change without notice.

Rev. September 3, 2016



## SOLAR ELECTRONICS COMPANY

*A Division of A.T. Parker, Inc.*

10866 Chandler Boulevard, North Hollywood, CA 91601 818-755-1700 sales@solar-emc.com