

ECOMPACT 4

Compact Test Station incl. Software

- Built according to:
 - IEC/EN 61000-4-2 (with ONYX16)
 - IEC/EN 61000-4-4 Ed. 1 & 2
 - IEC/EN 61000-4-5 Ed. 1 & 2
 - IEC/EN 61000-4-8 (with MFS 100)
 - IEC/EN 61000-4-9 (with MFS 100)
 - IEC/EN 61000-4-11 Ed. 1 & 2
 - IEC/EN 61000-4-29
- Surge voltage up to 4.2kV, 1.2/50 μ s
- Surge current up to 2.1kA, 8/20 μ s
- EFT Impulse voltage up to 4.2kV
- Integrated single phase coupling/decoupling network 16A for Surge and EFT
- Inrush current capability more than 500A
- Dip Levels: 0%, 40%, 70% & 80%
- Line max. current: 16A AC/DC



ECOUPLER 4

16A Three-Phase Coupling/Decoupling Network for SURGE & EFT Testing

- Built according to IEC/EN 61000-4-4 Ed. 1 & 2 and IEC/EN 61000-4-5 Ed. 1 & 2
- EUT voltage up to 440V/250V AC
- EUT current up to 16A per phase
- Test level max. 4.2kV / 2.1kA
- Fully automatic test routines

