

## NSG 3060 THE MODULAR SOLUTION FOR 6 KV APPLICATIONS



- **Modular, expandable system**
- **Surge voltage up to 6.6 kV allows over-testing**
- **Easy to use 7" color touch screen**
- **IEC and ANSI coupling methods**
- **Parameters can be changed while test is running**
- **Wide range of optional test accessories**
- **High accuracy switching technology meets ANSI coupling requirements**

Teseq's new NSG 3060 conducted immunity generator takes the proven, user-friendly design of the highly successful Modula series to a new level. This innovative design uses modular architecture to provide a versatile system that can be configured for basic testing needs and expanded to meet the needs of sophisticated test laboratories.

**Designed to fulfill requirements for CE mark and ANSI C62.41 testing**, the NSG 3060 performs tests for Combination wave surge, Ring wave and Electrical Fast Transient (EFT) pulses as well as Power Quality Testing (PQT). Extensive expansion capabilities enable the system to be configured for a much broader range of applications.

**Using state of the art components**, the self-contained modules set new standards with respect to switching and phase accuracy and exceed the existing standards' requirements. With its powerful processors, the NSG 3060 can completely fulfill the unique coupling requirements specified by ANSI C62.41. This standard requires that the pulse amplitude be adjusted for the phase position of the pulse on the AC mains, and for the amplitude of the mains voltage.

**A 7" touch panel display with superb contrast and color** is the most striking feature of the new NSG 3060. For fast and efficient data entry, input devices include an integrated keyboard and a thumbwheel with additional keys for sensitivity adjustment.

**The user-friendly graphic display speeds test setup.** Each parameter's value is highly visible and all settings can be quickly selected and modified with the generously sized touch input buttons. A stylus is not necessary, and ramp functions are programmed quickly and easily. Multi-step test procedures can be created and their sequence or parameter values changed easily.

**With Expert Mode users can make manual parameter changes** using the thumbwheel while a test is under way, providing an effective and fast method for identifying critical threshold values.

**The Test Assistance (TA) function** allows users to initiate standardized test with just a few "clicks" to achieve quick, reliable results in a development environment.

**The NSG 3060 has an Ethernet port for external PC control.** The Windows-based control software simplifies test programming and allows compilation of complex test sequences with diverse pulse types. Test reports can be generated during the test operation, allowing the operator to enter observations as the test progresses and increasing the efficiency of long-term tests.

# NSG 3060

## THE MODULAR SOLUTION FOR 6 KV APPLICATIONS

The NSG 3060 performs tests according to the following specifications:

### Combination wave pulse 1, 2/50 - 8/20 $\mu$ s (Hybrid-Surge pulse)

Pulse conforms to IEC/EN 61000-4-5 and ANSI (IEEE) 62.41

Parameter	Value
Pulse voltage (open circuit):	$\pm 200$ V to 6.6 kV (in 1 V steps)
Pulse current (short circuit):	$\pm 100$ A to 3.3 kA
Impedance:	2/12 $\Omega$
Polarity:	positive / negative / alternate
Pulse repetition:	10* .... 600 s (in 1 sec steps) 1 .... 10 min.
Test duration:	1 to 9999 pulses, continuous
Phase synchronization:	asynchronous, synchronous 0 to 359° (in 1° steps)
Coupling:	ANSI / IEC / external

\* Repetition rate depends on voltage:

200 to 4400 V = 10 s repetition time

4401 to 6600 V = 20 s repetition time

### Ringwave 0.5 $\mu$ s/100 kHz

Pulse conforms to IEC/EN 61000-4-12 and ANSI (IEEE) C62.41

Parameter	Value
Pulse voltage (open circuit):	$\pm 200$ V to 6.6 kV (in 1 V steps)
Pulse current (short circuit):	$\pm 16.6$ to $\pm 550$ A, $\pm 10\%$ $\pm 6.6$ to $\pm 220$ A, $\pm 10\%$ $\pm 1$ to $\pm 33$ A, $\pm 10\%$
Impedance:	12/30/200 $\Omega$
Polarity:	positive / negative / alternate
Pulse repetition:	10* .... 600 s (in 1 sec steps) 1 .... 10 min.
Test duration:	1 to 9999 pulses, continuous
Phase synchronization:	asynchronous, synchronous 0 to 359° (in 1° steps)
Coupling:	ANSI / IEC / external

\* Repetition rate depends on voltage:

200 to 4400 V = 10 s repetition time

4401 to 6600 V = 20 s repetition time

# NSG 3060

## THE MODULAR SOLUTION FOR 6 KV APPLICATIONS

### Burst (EFT) 5/50 ns

Pulse conforms to IEC/EN 61000-4-4

Parameter	Value
Pulse amplitude:	±200 V to 4.8 kV (in 1 V steps) - open circuit ±100 V to 2.4 kV (50 Ω matching system)
Burst frequency:	100 Hz to 1000 kHz
Polarity:	positive / negative / alternate
Repetition time:	1 ms to 4200 s (70 min)
Burst time:	1 μs to 1999 s, single pulse, continuous
Test duration:	1 s to 1000 h
Phase synchronization:	asynchronous, synchronous 0 to 359° (in 1° steps)
Coupling:	ANSI / IEC / external

### Dips & Interrupts

conforms to IEC/EN 61000-4-11, IEC/EN 61000-4-29

Parameter	Value
Dips & Interrupts:	From EUT voltage input to 0 V, 0% <sup>(1)</sup>
Uvar with optional variac:	depending on model (VAR 3005)
Uvar with step transformer:	0, 40, 70, 80% (INA 650x)
Peak inrush current capability:	500 A (at 230 V)
Switching times:	1 to 5 μs (100 Ω load)
Event time (T-Event):	20 μs to 1999 s, 1 to 300 cycles or 1 to 3'000 $\frac{1}{10}$ cycles
Test duration:	1 s to 70'000 min, 1 to 99'999 pulse, continuous
Repetition time:	40 μs to 35 min, 1 to 99'999 cycles
Phase synchronization:	asynchronous, synchronous 0 to 359° (in 1° steps)

(1) In combination with VAR 3005, effective minimal dip voltage ~8 V. As specified in IEC 61000-4-11, chapt. 5.1 a test voltage level from 0% to 20% of the rated voltage is considered as a total interruption.

### Variation test (with VAR 3005 only)

conforms to IEC/EN 61000-4-11

Parameter	Value
Uvar with optional variac:	up to 265 V (in 1 V steps) or up to 115% U <sub>in</sub> (in 1% steps)
Repetition time:	1 ms to 35 min, 1 to 99'999 cycles
Test duration:	1 ms to 5 s, 1 to 250 cycles (50 Hz); 1 to 300 cycles (60 Hz), abrupt
Repetition time:	10 ms to 10 s; 1 to 250 cycles (50 Hz), 1 to 300 cycles (60 Hz)
Test duration:	1 s to 70'000 min, 1 to 99'999 pulses, continuous
Phase synchronization:	asynchronous, synchronous 0 to 359° (in 1° steps)

# **NSG 3060**

## **THE MODULAR SOLUTION FOR 6 KV APPLICATIONS**

### **Pulsed magnetic field in conjunction with INA 753 and INA 701 or 702**

conforms to IEC/EN 61000-4-9

<b>Parameter</b>	<b>Value</b>
Field:	1 to 1200 A/m (in 1 A/m steps)
Polarity:	positive / negative / alternate
Repetition time:	5 s to 10 min (in 1 s steps)
Impedance:	2 $\Omega$
Coil factor	0.01 to 50.00
Test duration:	1 to 9'999 pulses; continuous
Phase synchronization:	asynchronous, synchronous 0 to 359° (in 1° steps)

### **Power magnetic field in conjunction with MFO 6501 / MFO 6502 and INA 701/702/703**

conform to IEC/EN 61000-4-8

Field:	1 to max. 40 A/m (in 1 A/m steps)
Frequency:	50/60 Hz
Coil factor:	0.01 to 99.99
Test duration:	1 to 9'999 pulses, continuous

# NSG 3060

## THE MODULAR SOLUTION FOR 6 KV APPLICATIONS

### Technical specification

Instrument supply	85 to 265 VAC, 50/60 Hz
Dimensions NSG 3060 WxHxD	449 (17.7") x 328 (12.9"; 7 HU) x 565 mm (22.2")
Weight NSG 3060	22 kg (48.5 lbs)

### Options

CDN 3061-x16	Single phase 270 V / 16 A automatic coupling decoupling networks
CDN 3063-x32	Three phase 480 V / 32 A automatic coupling decoupling networks
CDN 3063-S63	Three phase 480 V / 63 A automatic coupling decoupling network for Surge pulses up to 6,6 kV
CDN 3063-S100	Three phase 480 V / 100 A automatic coupling decoupling network for Surge pulses up to 6,6 kV
CDN 3083-B100 / -200	Manual 3-phase coupler for EFT / Burst (8 kV) only with EUT supply up to 690 VAC (1000 VDC) / 100 A / 200 A
CDN 3083-S100 / -200	Manual 3-phase coupler for Surge (8 kV) only (combination and ring wave) with EUT current up to 100 A / 200 A
CDN 3425	Burst EFT capacitive coupling clamp for data line coupling per IEC 61000-4
CDN 117/118	Coupling networks for signal-/data lines (surge)
CDN HSS-2	Coupling network for 2 kV surge pulse 1.2/50 $\mu$ s IEC/EN 61000-4-5 on unshielded symmetrical high speed telecom lines (Ethernet)
CAS 3025	Burst/EFT verification set
MD 200 / 200 A	Voltage differential probe 3.5 kV / 7 kV
MD 300	Current probe 5 kA

### Accessories for IEC/EN 61000-4-11

INA 6501	Manual step transformer, 16 AAC, 0/40/70/80%
INA 6502	Automatic step transformer, 16 AAC, 0/40/70/80%
VAR 3005-S16	Automatic single variable transformer, 1 x 16 A
VAR 3005-D16	Automatic double variable transformer, 2 x 16 A

### Accessories for IEC/EN 61000-4-8/-4-9

MFO 6501	Manual magnetic field option -4-8
MFO 6502	Automatic magnetic field option -4-8
INA 701	Magnetic field coil 1 x 1 m; with MFO max. 3.6 A/m -4-8; Surge* max. 1200 A/m -4-9
INA 702	Magnetic field coil 1 x 1 m, with MFO max. 40 A/m -4-8; Surge* max. 1200 A/m -4-9 *) Pulse shape adapter INA 752 needed to surge generator
INA 703	Magnetic field coil 1 x 1 m; max. 330 A/m -4-8
INA 752	Pulse shape adapter for IEC 61000-4-9

**Teseq AG**  
 Nordstrasse 11F 4542 Luterbach Switzerland  
 T +41 32 681 40 40 F +41 32 681 40 48  
 sales@teseq.com [www.teseq.com](http://www.teseq.com)

© February 2014 Teseq®  
 Specifications subject to change without notice.  
 Teseq® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, Teseq® does not assume any liability for errors or inaccuracies.

691-130E February 2014