

## CWS 500N1

### CONTINUOUS WAVE SIMULATOR, 80W



#### FOR TESTS ACCORDING TO ...

- > EN 300329
- > EN 300340
- > EN 300342-1
- > EN 300386 V1.3.2
- > EN 301489-1
- > EN 301489-17
- > EN 301489-24
- > EN 301489-7
- > EN 55024
- > EN 61000-4-6
- > EN 61000-6-1
- > EN 61000-6-2
- > IEC 60601-1-2
- > IEC 61000-4-6
- > IEC 61326
- > IEC 61850-3

#### CWS 500N1 - THE SINGLE BOX SOLUTION FOR RF CONDUCTED IMMUNITY TESTING







The CWS 500N1 is the most compact single box test equipment for testing conducted rf immunity as per IEC 61000-4-6 and related standards with a frequency range of 100kHz to 300MHz. Apart from the 1kHz 80% AM signal the CWS 500N1 also generates a 2 Hz 80% AM signal to test medical appliances and a 1 Hz PM signal with 50% duty cycle required to test safety equipment like fire alarms. Equipped with a 1 GHz current monitor the CWS 500N1 can be used up to 1 GHz by means of an external amplifier.

EM TEST supplies a large range of CDNs, EM clamp and current injection clamps as well as the corresponding calibration accessories. Full compliant levelling can be run from the front panel of the CWS 500N1 storing the results in 5 memory spaces available in the CWS 500N1.

#### HIGHLIGHTS

- > **Signalgenerator 9kHz to 1GHz**
- > **Amplitude modulation: 1Hz to 3kHz (0% to 95%)**
- > **Pulse modulation: 1Hz - 1kHz (10% to 90%)**
- > **Built-in amplifier, 100kHz to 300MHz**
- > **Built-in current monitor, 9kHz to 1GHz**

#### APPLICATION AREAS

- |   |  |
|---|--|
|  INDUSTRY  |  TELECOM          |
|  MEDICAL   |  RESIDENTIAL      |
|  BROADCAST |  RENEWABLE ENERGY |

## TECHNICAL DETAILS

### TEST LEVEL

|                     |  |
|---------------------|--|
| Output level        | 1V - max. 30V (emf)<br>all standard test levels are guaranteed with all coupling methods |
| Output power        | 80W (nominal)  |
| Output impedance    | 50ohm  |
| Harmonic distortion | < -20dBc at max.power  |

### TEST FREQUENCIES

|                      |  |
|----------------------|--|
| Sinus (CW)           | 100kHz to 300MHz   |
| Frequency bands      | 100kHz to 9.999MHz<br>10MHz to 99.99MHz<br>100MHz to 300MHz<br>in the Quick Start menu the step size can be selected by the operator |
| Unmodulated signal   | CW (continuous wave)   |
| Amplitude modulation | 1kHz, 80%AM as per IEC 61000-4-6<br>2Hz, 80%AM as per IEC 60601-1-2<br>400Hz, 80%AM  |
| Pulse modulation     | 1Hz, 50% duty cycle as per EN 50130-4  |

### MEASUREMENTS

|                  |  |
|------------------|--|
| Monitor          | Integrated RF power meter, measuring input for CDN and clamp calibration as well as current monitor for clamp applications |
| RF indicator     | LED indicating the RF output status  |
| LCD              | Online display of the test level and the preselected frequency value   |
| Cal data F1 - F5 | 5 internal memories to save calibration data, 1% step width as required by the standard                                    |

### TIME PARAMENTERS

|                        |                       |
|------------------------|-----------------------|
| Dwell time for CW & AM | td = 0.3s to 9,999s   |
| Dwell time for PM      | td = 3s to 9,999s     |
| Pause time             | tr = 0/0.3s to 9,999s |

### OUTPUT

|                  |                          |
|------------------|--------------------------|
| Direct RF output | BNC (on the front panel) |
|------------------|--------------------------|

### TEST ROUTINES

|                        |  |
|------------------------|--|
| Quick Start            | Immediate test start; easy-to-use and fast   |
| User Test routines     | Voltage sweep<br>Frequency sweep<br>Dwell time sweep                               |
| Standard Test routines | Level 1 to Level 3 (IEC 61000-4-6)<br>Automatic Level X to Level Y                 |
| Cal procedure          | Calibration of the complete test set-up, calibration data saved in internal memory |
| Service                | Service, set-up  |

### SIGNAL GENERATOR

|                  |                                  |
|------------------|----------------------------------|
| Output level     | -55dBm to 0dBm                   |
| Frequency range  | 9kHz to 1GHz                     |
| Output impedance | 50ohm                            |
| Direct RF output | To control an external amplifier |

### MEASUREMENTS FOR BCI APPLICATION

|         |   |
|---------|---|
| PM 1000 | 3-channel power meter up to 1GHz<br>- to measure the Forward power<br>- to measure the Reverse power<br>- to measure the injected current |
|---------|---|

### INTERFACE

|                    |  |
|--------------------|--|
| Serial interface   | USB  |
| Parallel interface | IEEE 488, addresses 1 to 30  |
| Fail 1             | BNC input; test will be stopped when active low  |
| Fail 2             | BNC input; test status will be saved (max. 10 events) when active low. Test will continue. |

### GENERAL DATA

|                    |  |
|--------------------|--|
| Dimensions, weight | 19"/3HU, approx. 17kg                                |
| Supply voltage     | 115V to 230V +10/-15%, 50/60Hz                       |
| Input power        | Max. 380W  |
| Power factor       | cos (phi) = 0.98 at max. output power as per IEC 555 |
| Fuses              | 2 x 6.3AT (115V) or 2 x 3.15AT (230V)                |
| Cooling            | Active cooling, air ventilation                      |
| Temperature        | 10°C to 40°C   |
| Rel. humidity      | Max. 85%, non condensing                             |

## TECHNICAL DETAILS

| OPTIONS      |  |
|--------------|--|
| ATT6/75      | 6dB attenuator, 75W  |
| ATT20/0.5    | 20db attenuator, 0.5W for the calibration of CDNs and clamps (included with the PM 1000)   |
| CDNs         | As per IEC 61000-4-6 (refer to separate list)  |
| Clamps       | EM clamp as per IEC 61000-4-6<br>Current injection clamps<br>Current monitoring clamps   |
| T-50         | 50ohm termination resistor for CDNs and clamps   |
| R-100x       | 150ohm-to-50ohm matching impedance for calibration   |
| Cal adapters | For all types of CDNs and clamps   |
| icd.control  | Extensive and most versatile remote control and reporting software. A standard library helps to configure the test setup.<br>Multiple interruption functions automated by IEEE instruments or manually.<br>Easy to use or expandable to complex test routines on the base of vector definitions. |

# COMPETENCE WHEREVER YOU ARE



## CONTACT EM TEST DIRECTLY

### Switzerland

EM TEST (Switzerland) GmbH > Sternenhofstraße 15 > 4153 Reinach > Switzerland  
 Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199  
 Internet: www.emtest.ch > E-mail: sales@emtest.ch

### Germany

EM TEST GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland  
 Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050  
 Internet: www.emtest.com > E-mail: info@emtest.de

### France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France  
 Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55  
 Internet: www.emtest.fr > E-mail: info@emtest.fr

### Poland

EM TEST Polska > ul. Ogrodowa 31/35, 00-893 Warszawa > Polska  
 Phone +48 (0)518 64 35 12  
 Internet: www.emtest.com/pl > E-mail: info.polska@emtest.de

### USA / Canada

EM TEST USA Inc. > 9250 Brown Deer Road > San Diego > CA 92121  
 Phone +1 (858) 699 1685 > Fax +1 (858) 458 0267  
 Internet: www.emtest.com > E-mail: tom.revesz@ametek.com

### P.R. China

EM TEST Representative Office Beijing > Rm 913, Leftbank > No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China  
 Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38  
 Internet: www.emtest.com > E-mail: emtestbj@public.bta.net.cn

### Malaysia

EM TEST (M) SDN BHD > Unit B2-6, Jalan Dataran SD2 > Dataran SD2, PJU9 > Bandar Sri Damansara > 52200 Kuala Lumpur > Malaysia  
 Phone +60 (03)62 73 22 01 > Fax +60 (03)62 74 22 01  
 Internet: www.emtest.com > E-mail: sales@emtest.com.my

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Technical data subject to change without further notice.