



Advanced Test Equipment Rentals

www.atecorp.com 800-404-ATEC (2832)

Model Number	Item Number	Description
8010	418010	Single Channel Desktop Gaussmeter
8030	418030	Three Channel Desktop Gaussmeter
Model Number	Item Number	Description
HAF81-2504-10	122300	Heavy Duty, Axial, DC electrical performance: 0.25% , 30kG, 1X, 0.250" stem thickness, 4" stem length, 10' cable length
HAF81-2504-10-T	122301	Heavy Duty, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.250" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
HAF81-2508-10	122302	Heavy Duty, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.250" stem thickness, 8" stem length, 10' cable length
HAF81-2508-10-T	122303	Heavy Duty, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.250" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
HAM81-2504-10	122304	Heavy Duty, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.250" stem thickness, 4" stem length, 10' cable length
HAM81-2504-10-T	122305	Heavy Duty, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.250" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
HAM81-2508-10	122306	Heavy Duty, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.250" stem thickness, 8" stem length, 10' cable length
HAM81-2508-10-T	122307	Heavy Duty, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.250" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
SAF81-1904-10	122308	Standard, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.187" stem thickness, 4" stem length, 10' cable length
SAF81-1904-10-T	122309	Standard, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.187" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
SAF81-1908-10	122310	Standard, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.187" stem thickness, 8" stem length, 10' cable length
SAF81-1908-10-T	122311	Standard, Axial, DC electrical performance: 0.25%, 30kG, 1X, 0.187" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
SAM81-1904-10	122312	Standard, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.187" stem thickness, 4" stem length, 10' cable length
SAM81-1904-10-T	122313	Standard, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.187" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
SAM81-1908-10	122314	Standard, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.187" stem thickness, 8" stem length, 10' cable length
SAM81-1908-10-T	122315	Standard, Axial, DC electrical performance: 0.15%, 30kG, 10X, 0.187" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
HTF81-0604-10	122318	Heavy Duty, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.060" stem thickness, 4" stem length, 10' cable length
HTF81-0604-10-T	122319	Heavy Duty, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.060" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
HTF81-0608-10	122320	Heavy Duty, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.060" stem thickness, 8" stem length, 10' cable length
HTF81-0608-10-T	122321	Heavy Duty, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.060" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
HTM81-0608-10	122322	Heavy Duty, Transverse, DC electrical performance: 0.15%, 30kG, 10X, 0.060" stem thickness, 8" stem length, 10' cable length
HTM81-0608-10-T	122323	Heavy Duty, Transverse, DC electrical performance: 0.15%, 30kG, 10X, 0.060" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
STF81-0402-10	122324	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.040" stem thickness, 2" stem length, 10' cable length
STF81-0402-10-T	122325	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.040" stem thickness, 2" stem length, 10' cable length, Temperature Compensated
STF81-0402-30-T	122325-3	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.040" stem thickness, 2" stem length, 30' cable length, Temperature Compensated
STF81-0404-10	122326	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.040" stem thickness, 4" stem length, 10' cable length
STF81-0404-10-T	122327	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.040" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
STM81-0402-10	122328	Standard, Transverse, DC electrical performance: 0.15%, 30kG, 10X, 0.040" stem thickness, 2" stem length, 10' cable length
STM81-0402-10-T	122329	Standard, Transverse, DC electrical performance: 0.15%, 30kG, 10X, 0.040" stem thickness, 2" stem length, 10' cable length, Temperature Compensated
STM81-0404-10	122330	Standard, Transverse, DC electrical performance: 0.15%, 30kG, 10X, 0.040" stem thickness, 4" stem length, 10' cable length
STM81-0404-10-T	122331	Standard, Transverse, DC electrical performance: 0.15%, 30kG, 10X, 0.040" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
STF81-0204-10	122332	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.020" stem thickness, 4" stem length, 10' cable length
STF81-0204-10-T	122333	Standard, Transverse, DC electrical performance: 0.25%, 30kG, 1X, 0.020" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
CTP81-3260-10	122334	Cryogenic, Transverse, DC electrical performance: 1.0%, 30kG, 10X, 0.312" stem thickness, 60" stem length, 10' cable length
CAP81-2560-10	122336	Cryogenic, Axial, DC electrical performance: 1.0%, 30kG, 10X, 0.250" stem thickness, 60" stem length, 10' cable length
HAR81-2508-10	122338	Heavy Duty, Axial, DC electrical performance: 1.0%, 100kG, 10X, 0.250" stem thickness, 8" stem length, 10' cable length
SAR81-1908-10	122339	Standard, Axial, DC electrical performance: 1.0%, 100kG, 10X, 0.187" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
HTR81-0608-10	122340	Heavy Duty, Transverse, DC electrical performance: 1.0%, 100kG, 10X, 0.060" stem thickness, 8" stem length, 10' cable length
MOS81-3204-10	122341	Magna, DC electrical performance: 1.0%, 1G, .001X, 0.312" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
MOS81-3204-30	122341-3	Magna, DC electrical performance: 1.0%, 1G, .001X, 0.312" stem thickness, 4" stem length, 10' cable length, Temperature Compensated
MOX81-2506-10	122342	Magna, DC electrical performance: 0.5%, 2G, .01X, 0.250" stem thickness, 6" stem length, 10' cable length
ZOA83-3208-10	122343	3-Axis, DC electrical performance: .25%, 10kG, 1X, 0.312" stem thickness, 8" stem length, 10' cable length
ZOA83-3208-10-T	122344	3-Axis, DC electrical performance: .25%, 10kG, 1X, 0.312" stem thickness, 8" stem length, 10' cable length, Temperature Compensated
ZOA83-3208-30	122343-3	3-Axis, DC electrical performance: .25%, 10kG, 1X, 0.312" stem thickness, 8" stem length, 30' cable length
ZOA83-3208-30-T	122344-3	3-Axis, DC electrical performance: .25%, 10kG, 1X, 0.312" stem thickness, 8" stem length, 30' cable length, Temperature Compensated
SAF81-1902-10-T	122335	Standard, Axial, DC electrical performance: .25%, 30kG, 1X, 0.187" stem thickness, 2" stem length, 10' cable length, Temperature Compensated
FTM81-0215-10-T	122337	Flexible, Transverse, DC electrical performance: .15%, 30kG, 10X, 0.020" stem thickness, 15" stem length, 10' cable length, Temperature Compensated
STD81-0404-10	122347	Standard, Transverse, DC electrical performance: 0.50%, 30kG 1X, 0.040" stem thickness, 4" stem length, 10' cable length