



Welch DryFast Ultra Plus

Model 2040


Meet Welch's new dry vacuum pump, providing an ultimate vacuum below 1 TORR - one of the highest vacuum performances from any 2-stage 2-head corrosion resistant diaphragm pump on the global market for your vacuum manifold (Schlenk lines), rotary evaporator or vacuum concentrator applications.



SPECIFICATION

MODEL	2040
Free Air Displacement, lpm	40
Ult. Vac. Pressure, torr (mbar)	0.75 (1)
Maximum Vacuum, in. Hg	29.9
Number heads/Stages	2/2
Motor Horsepower, HP (watts)	1/5 (150)
Adjustable Vac/Gas Ballast	Yes
Tubing Needed, I.D., in (mm)	1/4 (7)
Intake(Exhaust) Thread NPT	M14 (1/8)
Weight lbs.(kg)	21.25 (9.6)
Overall Dimensions, LxWxH in.(cm)	13.8x6.8x8.8 (35x17x22)
Ship Weight, lbs (kg)	25 (11.3)
Shipping Carton Dimensions, LxWxH in.(cm)	21x14x15 (52x35x37)
ORDERING INFORMATION	2040
Wired for 115V, 60Hz, 1Ph	2040B-01
Wired for 230V, 50/60Hz, 1Ph	2040C-02

PUMPING SPEED CURVE



Depend on Welch to deliver the highest performance, most durable vacuum pumps

AMERICAS
Gardner Denver Thomas Inc.
1601 Feehanville Drive
Suite 550
Mt. Prospect, IL 60056
USA

Tel: +1 847 676 8800
welch.na@irco.com



www.welchvacuum.com