



NOVA

Dependable Gas Analysis Solutions

5460 SERIES

PORTABLE ENGINE EXHAUST ANALYZERS



APPLICATIONS

For spot-checking engine exhaust emissions for diesel, gasoline, propane, or natural gas powered 2 and 4 cycle engines. Analysis of carbon monoxide (CO), hydrocarbons (HC's), carbon dioxide (CO₂), oxygen (O₂), nitric oxide (NO), nitrogen dioxide (NO₂), and sulfur dioxide (SO₂).

FEATURES

- Same rugged easy-to-use design as traditional Nova portable analyzers, but approx. 65% smaller and 50% lighter
- Fast warm up and accurate response
- Rugged touch-screen display of gas readings
- Solid state infrared detectors for % CO, CO₂, and HC's
- Electrochemical sensors for O₂, ppmCO, NO, NO₂, and SO₂
- Rechargeable lithium ion battery; up to 8hrs use per charge (recharge from vehicle or from AC adapter)
- Provided with sample filter, and flexible sample probe with 12 ft. of hose, built-in sample pump and automatic condensate removal
- Local USB data logging creates CSV files
- Built-in trouble-shooting prompts
- Meets Bar 97 and ISO 3930/OIML R99, Class O specifications

OPTIONS

- 4-20mA output in external adaptor
- Built-in printer, with remote print button
- PPM CO in place of % CO measurements for recent engine designs with lower emissions



5460 series with optional printer



Standard engine exhaust probe with flexible tip

CALIBRATION

- Zero on air
- Span on analyzed calibration gases

DESCRIPTION

The Nova 5640 Series Portable Engine Exhaust Analyzers are built on the NOVANOW next-generation rugged portable platform. This series has been designed for accuracy, reliability, ease of use and ease of service, providing a detailed spot-check analysis of engine exhaust gas composition. The 5460 uses customer-replaceable electrochemical sensors that respond quickly to the O₂, ppmCO, NO, NO₂, and SO₂ present in the exhaust gas sample. The O₂ sensor life expectancy is typically 3-4 years. The CO, NO, NO₂, and SO₂ sensor life is typically 2-3 years. The infrared CO₂ and HCs sensors should not need to be replaced under normal conditions of use.

A rechargeable lithium ion battery provides enough power for about 8 hours of continuous operation and the analyzer can be used while it is being recharged. The 5460 series integrated case is small but rugged, and dust & water resistant when closed. The 5460 Series Analyzers are complete with built-in sampling pump, flow meter, automatic condensate removal, filters, PTFE liquid blocker, 12 ft. (4m) sampling hose, and stainless steel engine exhaust probe with pre-filter. Also included are a cigarette lighter power plug and remote printer actuator button for printer-equipped models.

MODELS

- 5461K: any single gas
- 5462K: CO and HC's
- 5463K: CO, CO₂, and HC's
- 5464K: O₂, CO, CO₂, and HC's
- 5465K: O₂, CO, CO₂, HC's, and NO_x (as NO)
- 5466K: O₂, CO, CO₂, HC's, and NO & NO₂

SPECIFICATIONS

Nova reserves the right to specification changes which may occur with advances in design without prior notice.

Description

Method of Detection:

CO (standard range), CO₂, and HC by infrared detector
CO (low range), NO, NO₂, SO₂, and O₂ by electrochemical sensor.

Available Ranges:

0-5.00% / 10.00% CO (standard range)	0-25.0% O ₂
0-2,000 / 5,000 / 10,000 PPM CO (low range)	0-20.0% CO ₂
0-2,000 / 5,000 PPM NO _x (as NO)	0-800 PPM NO ₂
0-2,000 / 5,000 / 10,000 (as hexane)	0-2,000 PPM SO ₂
0-20,000 PPM HC's (as propane)	

Resolution:

0.1% on % ranges, 0.01% on standard range CO, 1 PPM on most PPM ranges

Accuracy and Repeatability:

±1% of full scale for O₂, CO, CO₂, and HCs; ±2% of full scale for NO_x and SO₂

Drift:

< ± 1% in 8 hours after full warmup

Response Time (T90):

8-10 seconds

Ambient Temperature Range:

0 to 40°C

Linearity:

±1.0% of full scale each gas measured

Size And Weight:

approx. 26 x 18 x 13 cm @ 3.4 kg (10" x 7" x 5" @ 7.5lbs)

Power:

115 VAC or 220VAC, 50/60Hz for recharging. Also 12VDC for cigarette lighter socket

Optional Outputs:

CSV log files written to USB memory stick



NOVA ANALYTICAL SYSTEMS
(A UNIT OF TENOVA GOODFELLOW INC.)

IN USA:

1925 Pine Avenue • Niagara Falls, NY • 14301
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937

IN CANADA:

270 Sherman Avenue North • Hamilton, ON • L8L 6N5
Tel: 905.545.2003 • Fax: 905.545.4248

email: sales@nova-gas.com

websales@nova-gas.com



www.nova-gas.com